

MATERIAL SAFETY DATA SHEET

FOR PRINTING INK AND RELATED MATERIALS

INFORMATION ON THIS FORM IS PROPRIETARY INFORMATION AND FURNISHED SOLELY FOR THE USE OF OUR CUSTOMERS

DATE OF PREP. 5.15.04 PREPARED BY RUNE E. GOOP

HAZARD RATINGS

Minimal 0
Slight 1
Moderate 2
Serious 3
Severe 4

| | |
|--------------|---|
| HEALTH | 2 |
| FLAMMABILITY | 1 |
| REACTIVITY | 0 |

Section I

MANUFACTURER'S NAME: SCHWAAB, INC.
STREET ADDRESS: 11415 WEST BURLEIGH STREET CITY, STATE AND ZIP CODE: MILWAUKEE WI 53226
EMERGENCY TELEPHONE NUMBER: CHEMTREC 1.800.424.9300 (ALWAYS AVAILABLE). 1.414.771.4150
PRODUCT CLASS: preinked rubber stamp precursor
TRADE NAME: _____ MANUFACTURER'S CODE IDENTIFICATION: _____

Section II - HAZARDOUS INGREDIENTS

| Ingredient: | Hazard Data: |
|---|---|
| DYECOLORED POLYVINYL CHLORIDE PLASTISOL COMPOUND | IRRITANT. THERE ARE NO KNOWN HAZARDOUS COMPONENTS ABOVE REGULATORY THRESHOLDS IN THIS PRODUCT |

Section III - PHYSICAL DATA

| | | | |
|--|--|--|----------------------|
| BOILING RANGE °F N.A. CONGELS WHEN HEATED | VAPOR DENSITY: HEAVIER <input checked="" type="checkbox"/> vs. air LIGHTER <input type="checkbox"/> | LIQUID DENSITY: HEAVIER <input type="checkbox"/> vs. water LIGHTER <input type="checkbox"/> | TYPE OF ODOR MILD |
| APPEARANCE COLORED VISCIOUS LIQUID | EVAPORATION RATE FASTER <input type="checkbox"/> vs. Butyl Acetate SLOWER <input checked="" type="checkbox"/> | PERCENT VOLATILE WT. 0 | |

Section IV - FIRE & EXPLOSION DATA

| | | | |
|-----------------------------|-------------------------|---|----------|
| FLAMMABILITY CLASSIFICATION | OSHA 60MB. III B DOT | FLASH POINT °F NOT DETERMINED (Method Used) | LEL NONE |
|-----------------------------|-------------------------|---|----------|

EXTINGUISHING MEDIA:

FOAM "ALCOHOL" FOAM CO2 DRY CHEMICAL WATER FOG OTHER

UNUSUAL FIRE AND EXPLOSION HAZARDS

NONE

SPECIAL FIREFIGHTING PROCEDURES

NONE

Section V - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE

SKIN: may cause redness or itching
EYES: PROCESSING VAPORS MAY CAUSE REDNESS & TEARING
INHALATION OF PROCESSING VAPORS MAY CAUSE NASAL & RESPIRATORY IRRITATION
INGESTION: CAN CAUSE NAUSEA & DIARRHEA

PRIMARY ROUTE(S) OF ENTRY: DERMAL INHALATION

EMERGENCY AND FIRST AID PROCEDURES

SKIN: CLEAN WITH SOAP AND WATER
EYES: FLUSH WITH WATER 15 MIN. KEEPING EYELIDS APART
INHALATION: REMOVE PERSON TO FRESH AIR. CALL PHYSICIAN
INGESTION: GIVE 2 GLASSES OF WATER INDUCE VOMITING. CALL PHYSICIAN

Section VI - REACTIVITY DATA

PRODUCT STABILITY STABLE UNSTABLE

CONDITIONS TO AVOID CONTACT WITH STRONG OXIDIZERS, & STRONG ACIDS, & STRONG ALKALINE CHEMICALS

Section VII - SPILL OR LEAK PROCEDURES

PROCEDURE WHEN MATERIAL SPILLED OR RELEASED

COLLECT FOR DISPOSAL

WASTE DISPOSAL METHOD ACCORDING TO LOCAL REGULATIONS. INCINERATION NOT RECOMMENDED

Section VIII - SPECIAL PROTECTION INFORMATION

VENTILATION LOCAL EXHAUST

PROTECTIVE GLOVES IMPERVIOUS GLOVES. VINYL GLOVES NOT RECOMMENDED

RESPIRATORY PROTECTION NIOSH APPROVED RESPIRATOR EYE PROTECTION SAFETY GOGGLES

OTHER PROTECTIVE EQUIPMENT CLOTHING AS NEEDED TO PREVENT SKIN CONTACT

Section IX - SPECIAL PRECAUTIONS

HANDLING AND STORING

KEEP AWAY FROM FOOD, CHILDREN, AND HEAT SOURCES

STORE IN TIGHT CONTAINERS IN A COOL PLACE FOR MAXIMUM STORAGE LIFE

OTHER PRECAUTIONS

APPLY GOOD INDUSTRIAL HYGIENE